



serie  
UCF200

CRB®



Bearing unit No.	Shaft Dia.	Dimension /mm/									Bolt used	Bearing No.:	Housing No.:	Weight kg
	d	a	e	i	g	l	S	Z	Bi	n				
UCF 201	12	86,0	64	15	12	25,5	12	33,3	31,0	12,7	M10	UC 201	F 201	0,63
UCF 202	15	86,0	64	15	12	25,5	12	33,3	31,0	12,7	M10	UC 202	F 202	0,63
UCF 203	17	86,0	64	15	12	25,5	12	33,3	31,0	12,7	M10	UC 203	F 203	0,63
UCF 204	20	86,0	64	15	12	25,5	12	33,3	31,0	12,7	M10	UC 204	F 204	0,63
UCF 205	25	95,0	70	16	14	27	12	35,7	34,0	14,3	M10	UC 205	F 205	0,82
UCF 206	30	108,0	83	18	14	31	12	40,2	38,1	15,9	M10	UC 206	F 206	1,10
UCF 207	35	117,0	92	19	16	34	14	44,4	42,9	17,5	M12	UC 207	F 207	1,50
UCF 208	40	130,0	102	21	16	36	16	51,2	49,2	19,0	M14	UC 208	F 208	1,90
UCF 209	45	137,0	105	22	18	38	16	52,2	49,2	19,0	M14	UC 209	F 209	2,30
UCF 210	50	143,0	111	22	18	40	16	54,6	51,6	19,0	M14	UC 210	F 210	2,50
UCF 211	55	162,0	130	25	20	43	19	58,4	55,6	22,2	M16	UC 211	F 211	3,40
UCF 212	60	175,0	143	29	20	48	19	68,7	65,1	25,4	M16	UC 212	F 212	4,40
UCF 213	65	187,0	149	30	20	50	19	69,7	65,1	25,4	M16	UC 213	F 213	5,30
UCF 214	70	193,0	152	31	24	54	19	75,4	74,6	30,2	M16	UC 214	F 214	6,00
UCF 215	75	200,0	159	35	24	57	19	79,5	77,8	33,3	M16	UC 215	F 215	6,60
UCF 216	80	208,0	165	35	24	59	23	84,3	82,6	33,3	M20	UC 216	F 216	7,50
UCF 217	85	220,0	175	36	26	63	23	87,6	85,7	34,1	M20	UC 217	F 217	9,10
UCF 218	90	235,0	187	42	26	70	23	98,3	96,0	39,7	M20	UC 218	F 218	11,30