



serie  
UCFC



SR type seal



TRL type seal

Bearing unit No.	Shaft	Dimension /mm/												Bolt used	Bearing No.:	Housing No.:	Weight kg
	diameter																
	/mm/	a	p	e	i	l	S	j	K	g	Z	Bi	n				
UCFC 201	12	100,0	78,0	55,1	10	25,5	12	5	7	20,5	28,3	31,0	12,7	M10	UC 201	FC 201	0,78
UCFC 202	15	100,0	78,0	55,1	10	25,5	12	5	7	20,5	28,3	31,0	12,7	M10	UC 202	FC 202	0,78
UCFC 203	17	100,0	78,0	55,1	10	25,5	12	5	7	20,5	28,3	31,0	12,7	M10	UC 203	FC 203	0,78
UCFC 204	20	100,0	78,0	55,1	10	25,5	12	5	7	20,5	28,3	31,0	12,7	M10	UC 204	FC 204	0,78
UCFC 205	25	115,0	90,0	63,6	10	27	12	6	7	21	29,7	34,0	14,3	M10	UC 205	FC 205	0,95
UCFC 206	30	125,0	100,0	70,7	10	31	12	8	8	23	32,2	38,1	15,9	M10	UC 206	FC 206	1,40
UCFC 207	35	135,0	110,0	77,8	11	34	14	8	9	26	36,4	42,9	17,5	M12	UC 207	FC 207	1,70
UCFC 208	40	145,0	120,0	84,8	11	36	14	10	9	26	41,2	49,2	19,0	M12	UC 208	FC 208	2,00
UCFC 209	45	160,0	132,0	93,3	10	38	16	12	10	26	40,2	49,2	19,0	M14	UC 209	FC 209	2,80
UCFC 210	50	165,0	138,0	97,6	10	40	16	12	14	28	42,6	51,6	19,0	M14	UC 210	FC 210	3,00
UCFC 211	55	185,0	150,0	106,1	13	42	19	12	15	31	46,4	55,6	22,2	M16	UC 211	FC 211	4,00
UCFC 212	60	195,0	160,0	113,1	17	48	19	12	15	36	56,7	65,1	25,4	M16	UC 212	FC 212	4,70
UCFC 213	65	205,0	170,0	120,2	16	50	19	14	15	36	55,7	65,1	25,4	M16	UC 213	FC 213	5,40
UCFC 214	70	215,0	177,0	125,1	17	54	19	14	18	40	61,4	74,6	30,2	M16	UC 214	FC 214	6,80
UCFC 215	75	220,0	184,0	130,1	18	56	19	16	18	40	62,5	77,8	33,3	M16	UC 215	FC 215	7,30
UCFC 216	80	240,0	200,0	141,4	18	58	23	16	18	42	67,3	82,6	33,3	M20	UC 216	FC 216	8,90
UCFC 217	85	250,0	208,0	147,1	18	63	23	18	20	45	69,6	85,7	34,1	M20	UC 217	FC 217	10,40
UCFC 218	90	265,0	220,0	155,5	22	68	23	18	20	50	78,3	96,0	39,7	M20	UC 218	FC 218	13,00